



Product Information

Valvoline Copper Spray

Anti-seize compound
Wide temperature range capability
Improves thread sealing
Protect battery terminals
Easy to remove

Anti-Seize compound

Valvoline copper spray is an excellent anti-seize compound that performs well over an extremely wide temperature range (-30°C +1200°C). Use on nuts or bolts for easy installation and removal. Valvoline copper spray seals threads from damaging water ingress and corrosion development. A thin coating of Valvoline copper spray protects battery terminals from corrosion.

Easy to use

Shake well before using. Spray holding the can upright 15-20 cm. from the surfaces being treated.

Technical data

Appearance	Copper colored paste
Specific Gravity	0.67

This information only applies to products manufactured in the following location(s): Europe

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.



Product Information

PROBLEM	CAUSE	PERFORMANCE	APPLICATION
Seized bolts and nuts that are subjected to extreme temperatures.	Heat, cold and corrosion can make nuts and bolts almost impossible to remove.	Valvoline Copper Spray enables nuts and bolts to be fitted and removed even after being subjected to temperatures ranging from below 0 °C. to over 1000 °C.	Shake well before using. Spray holding the can upright 15-20 cm. from the surfaces being treated.

This information only applies to products manufactured in the following location(s): Europe

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.