

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Dipperstick Grease

607/01

Valvoline Dipperstick Grease is very adhesive to metal surfaces, resists water washing and prevents rust and corrosion. The product possesses excellent wear-resisting properties and contains graphite which makes it suitable for working in damp, or even wet conditions. It withstands high temperatures without excessive softening and is easy to apply at low temperatures. Excellent load carrying capacity and good corrosion preventive properties. Recommended for lubrication of dippersticks, open gears, cables, and coupling devices of trucks and trailers.

Performance levels		Viscosity Grade
NLGI grade	2	
4-ball Weld Load test (DIN 51350)	>790 kg.	

Typical Properties	
NLGI grade	2
Soap type	complex
Worked penetration (60 strokes)	265-295
Oil viscosity: mm ² /s@ 100°C	45
Oil viscosity: mm ² /s@ 40°C	660
Dropping point °C	min. 250
Application temperature °C	-20 to +140
Colour	dark grey/black

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
Nov. 1, 2002	Nov. 1, 2004		AdG	162 G9

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.