

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline DuraBlend Chainsaw 2T

502/04

Valvoline DuraBlend Chainsaw 2T is a synthetic blend lubricant especially formulated with unique base-oils and additives to provide enhanced oil film strength for severe operating conditions encountered by high speed light and heavy chainsaw equipment. The oil is prediluted for easier mixing and may be used in both injector and pre-mix systems. Use fuel/oil mixtures as specified by the manufacturer of the engine.

Approvals/performance levels

API TC
JASO FD
ISO L-EGD
Husqvarna 242/346

Typical Properties

Viscosity, mm ² /s @ 100 °C	9.4
Viscosity, mm ² /s @ 40 °C	60
Viscosity Index	140
Sulphated Ash, wt. %	0.12
TBN; mg KOH/g (ASTM D-2896)	3.1
Pour Point, °C	-42
Specific Gravity @ 15/15°C	0.867
Flash Point, PMCC, °C	90

This information only applies to products manufactured in the following location(s): Dordrecht.

Effective Date:	Replaces:	Author's Initials:	Code
30-5-2006	502/03	AdG	

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.