

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

DuraBlend™ Gear Oil GL-5 LS

216/03

DuraBlend Gear Oil GL-5 LS is a synthetic blend gear oil specially formulated for use in virtually all Limited Slip, hypoid and other gears where the manufacturer specifies an API GL-5 type lubricant. The base oils and special additives in this formulation reduce noises in differentials while the excellent EP properties protect the gears against wear under all conditions. Recommended for passenger cars, trucks and buses.

Approvals/Performance levels	Viscosity Grade
API GL-5 LS	75W90
MIL-L-2105D	75W90

Typical Properties	75W90
Viscosity, mm ² /s @ 100 °C	16.0
Viscosity, mm ² /s @ 100°C. after shearing (CEC: L-45-T-93)	stay-in-grade
Viscosity, mm ² /s @ 40 °C	110
Viscosity Index	156
Viscosity, mPa.s -40 °C	<150.000
TAN; mg KOH/g (ASTM D-664)	2.3
Pour Point, °C	-45
Specific Gravity @ 15/15°C	0.879
Flash Point, COC, °C	158

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
20-8-2010	216/02	AdG	

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.