

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE Engine Stop Leak

EC6/001

Reduces oil leaks from main bearing seals
Helps to keep seals soft and pliable
Compatible with motor oils
Improves engine oil viscosity index
Contains no harmful solvents or solids

Helps stop engine oil leaks

Elastomeric seals in contact with hot oil tend to shrink, harden and become less pliable. As a result, oil begins to leak out. One alternative is to replace the leaking seals, another is simply to add Valvoline engine stop leak to the engine oil. Valvoline engine stop leak contains a synthetic seal swell additive to swell seals back to their original size and help them regain pliability. Valvoline engine stop leak will only swell seals until they reach their original size. If seals were allowed to swell beyond their original size, they would become weak and possibly leak more. Valvoline engine stop leak also contains a viscosity index improver to reduce leaking until the seals are revitalized. If seals are broken or cracked, they must be replaced to stop the leak. Valvoline engine stop leak will not repair broken or cracked seals.

Easy to use

Add one bottle of Valvoline engine stop leak to the engine oil and allow the engine to idle for 10 minutes to ensure adequate mixing. If leak persists after 500 km., seals may be cracked or broken and should be replaced.

Technical data

Appearance	Clear Amber Liquid
Specific Gravity	0.880

Comment

Valvoline engine stop leak can be used in diesel or petrol powered vehicles.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

PROBLEM	CAUSE	PERFORMANCE	APPLICATION
Excessive oil and grime build up on the outside of the engine, reduced engine level oil, unsightly oil marks on the driveway.	Oil leakage through engine oil seals.	Helps reduce or eliminates oil leaks from gaskets and O-rings. Rejuvenates seals to original size and flexibility.	Add to crankcase oil when engine is warm. Idle for 10 min. If leak persists after 500 km of driving, the gaskets may be cracked or broken and require replacement.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.