



# Product Information

---

## Valvoline Glue Spray

Valvoline Glue Spray is an adhesive for rapid bond formation of porous surfaces. The product is formulated for bonding of: textile, leather, cardboard, foam rubber, imitation leather, vinyl, carpets, etc. Not suitable for polystyrene.

### Rapid bonding

If used in the right way, hightec spray adhesive dries very rapidly. Apply the product on both objects and press in position after drying. At room temperature the product dries in 2 minutes.

### Easy to use

Shake well before use.  
Spray evenly at a distance of 20-25 cm. Spray both surfaces and allow drying for 2 minutes, then press in position. For flexible foam, spray both surfaces and allow drying for 30 sec. then press in position.  
After spraying, hold the aerosol spray can in upside down position and spray until the spray is free of adhesive.

### Technical data

Appearance	Light Yellow
Odor:	Typical
Solvents:	Aliphatic Hydro carbons
Aerosol:	Propane/Butane
Temperature:	10-35°C.
Storage:	Cool and dry.

### Comments

Always read and follow warning labels.

This information only applies to products manufactured in the following location(s): Europe

*The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.*