

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Lawnmower Oil

503/03

Valvoline Lawnmower Oil is a premium lubricant specially developed for use in all 4-cycle lawn mowers, rotary cultivators, small tractors, floor cleaning machines and other similar equipment operating in a high revving environment. This product keeps the engine clean and protects against wear and corrosion.

Approvals/performance levels	Viscosity Grade
API SG/CD	30

Typical Properties	30
Viscosity, mm ² /s @ 100 °C	10.5
Viscosity, mm ² /s @ 40 °C	83
Viscosity Index	112
Viscosity, mPa.s -20°C	
Viscosity, mPa.s -10 °C	3000
Sulphated Ash, wt. %	1.20
TAN; mg KOH/g (ASTM D-664)	2.2
TBN; mg KOH/g (ASTM D-2896)	9.0
Pour Point, °C	-21
Specific Gravity @ 15/15°C	0.890
Flash Point, COC, °C	232
Noack Evaporation, wt. %	13.5

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
13-08-2001	13-08-2003		SH	

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.