

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Lithium No.2 – EP Grease

602/04

Valvoline Lithium No.2 – EP Grease is a universal, lithium EP grease, developed for lubrication of automotive and industrial equipment. Valvoline Lithium No.2 - EP Grease can be applied over a wide temperature range. The product has a good water resistance and protects against rust and corrosion. Mechanically very stable and easily pumpable due to its smooth structure.

Approvals/performance levels		Viscosity Grade
NLGI grade	2	
SKF Emcor test	Pass.	
Copper Corr. Test ASTM D-4048		

Typical Properties	
NLGI grade	2
Soap type	lithium
Worked penetration (25°C)	265-295
Oil viscosity: mm ² /s@ 100°C	16.5
Oil viscosity: mm ² /s@ 40°C	200
Dropping point °C	198
Flowpressure test @ -20°C	Pass.
Application temperature °C	-20 to +140
Colour	Yellow/amber
Structure	smooth
Specific Gravity @ 15°C.	0.950

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
Apr. 15, 2004	602/03	AdG	Li

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.