

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Moly Fortified MP Grease

603/04

Valvoline Moly Fortified MP Grease is a universal, lithium EP grease with molybdenum disulphide to reduce friction. Developed for lubrication of automotive and industrial equipment specially when working under wet circumstances. Valvoline Moly Fortified Multi Purpose Grease can be applied over a wide temperature range, and can be used for chassis lubrication of trucks, tractors, bulldozers and other on- and off the road and industrial equipment. The product is mechanically very stable and due to its smooth structure easily pumpable.

Approvals/performance levels	Viscosity Grade
NLGI grade	2
Water washout test % at 80°C.	pass

Typical Properties

NLGI grade	2
Soap type	lithium
Worked penetration (25°C)	265-295
Oil viscosity: mm ² /s@ 100°C	14.1
Oil viscosity: mm ² /s@ 40°C	152
Dropping point °C	195
Flowpressure test @ -30°C	Pass.
Application temperature °C	-15 to +120
Colour	greyblack
Structure	smooth
Specific Gravity @ 15°C.	0.950

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
Apr. 15, 2004	603/04	AdG	

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.