

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil – Motorcycle Motor Oils

Version: 305/04

Motorcycle Oil 2T

Premium 2-cycle motorcycle engine oil for use in both oil injection and pre-mix systems – Formulated to prevent spark plug fouling and carbon deposits

Motorcycle Oil 2T is a premium 2-cycle motorcycle engine oil for use in both oil injection and pre-mix systems. It reduces smoke and provides exceptional protection under the most severe conditions. Can be used in motorcycles, go-karts and all other two-stroke engines.

Approvals/Performance levels

SAE
API: TC
JASO: FB
ISO: L-EGB

Applications

For use in both oil injection and pre-mix systems

Pre-diluted for easier mixing and may be used for both injector and pre-mix applications.

Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 50:1.

For use in motorcycles, go-karts and all other two-stroke engines.

Features and Benefits

Wear protection

Burns cleaner to reduce deposits and eliminate smoke and engine wear.

Engine cleanliness

Quality detergents prevent spark plug fouling and combat carbon deposit build-up.

Breakdown resistance

Shear stable viscosity improvers help resist oil film breakdown.

Multi-purpose use

Suitable for leisure, transport, and day-to-day riding.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Motorcycle Oil 2T	
SAE Viscosity Grade	
Viscosity , mm ² /s @ 100 °C. ASTM D-445	9.2
Viscosity , mm ² /s @ 40 °C. ASTM D-445	65
Viscosity Index ASTM D-2270	118
TBN , mg KOH/g ASTM D-2896	1.2
Pour Point , °C ASTM D-5950	-36
Specific Gravity @ 15.6°C. ASTM D-4052	0.874
Flash Point , COC, °C. ASTM D-92	96

This information only applies to products manufactured in the following location(s): Europe

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 305/03

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.