

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil – Motorcycle Oils

Version: 309/05

Valvoline™ Motorcycle Fork Oil SAE 10W

Synthetic blend specially formulated to provide superior performance in motorcycle front forks and shock absorbers -- Excellent protection against oxidation, corrosion, foaming and wear.

Motorcycle Fork Oil is a *competition synthetic blend* specially formulated to provide superior performance in motorcycle front forks and shock absorbers in both on-road and off-road usage. The product can be used all year-round

Approvals/Performance levels

SAE 10W
ISO: 32

Check owner's manual before use.

Applications

Provides excellence performance in motorcycle front forks and shock absorbers for both on-road and off-road usage.

Can be used in motorcycle suspension systems.

Year-round use.

Features and Benefits

Wear protection

Strong oil film protects the suspension system against wear, oxidation, corrosion and foaming.

Suspension system cleanliness

Keeps the suspension system clean and protects against foaming.

Breakdown resistance

Shear stable viscosity improvers help resist oil film breakdown.

Year round use

Suitable the whole year round and day-to-day riding.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Motorcycle Fork Oil	
SAE Viscosity Grade	10W
Viscosity, mm ² /s @ 100 °C. ASTM D-445	6.0
Viscosity, mm ² /s @ 40 °C. ASTM D-445	34
Viscosity Index ASTM D-2270	118
Pour Point, °C ASTM D-5950	-39
Specific Gravity @ 15.6°C. ASTM D-4052	0.863
Flash Point, COC, °C. ASTM D-92	234

This information only applies to products manufactured in the following location(s): Europe

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 309/04

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.