



Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Multi Purpose Grease

601/04

Valvoline Multi Purpose Grease is a universal, heavy duty lithium complex EP grease, developed for lubrication of automotive and industrial equipment, like trucks, road-building equipment, and industrial machinery. The product is also suitable to lubricate marine equipment working in damp atmosphere. Valvoline Multi Purpose Grease can be applied over a wide temperature range, is mechanically very stable and due to its smooth structure easily pumpable.

Approvals/performance levels	Viscosity Grade
NLGI grade	2
Emcor test DIN 51802	pass
Copper corr. Test ASTM D-4048	pass

Typical Properties	
NLGI grade	2
Soap type	Lithium-complex
Worked penetration (25°C)	265-295
Oil viscosity: mm ² /s@100°C	15.5
Oil viscosity: mm ² /s@ 40°C	160
Dropping point °C	300
Copper corrosion test ASTM 4048	1b
Application temperature °C	-20 to +180
Colour	Red
Specific Gravity @ 15.6°C.	0.950
Structure	Smooth/tacky

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
Apr. 15, 2004	601/03	AdG	F MP

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.