

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Semi Fluid Grease 00

604/04

Valvoline Semi Fluid Grease 00 is a lithium grease of soft consistency for lubrication of bearings and closed industrial gearboxes where a semi fluid grease is required. Valvoline Semi Fluid Grease 00 is suitable for automatic lubrication systems of trucks and in the industry where a double zero grease is prescribed. The product has extreme pressure properties and is mechanically very stable. Due to its smooth structure, the grease is easily pumpable.

Approvals/performance levels		Viscosity Grade
NLGI grade	00	
SKF Emcor test	pass	
Copper corr. Test ASTM D-4048	pass	

Typical Properties	
NLGI grade	00
Soap type	lithium
Worked penetration (25°C)	400-430
Oil viscosity: mm ² /s@ 100°C	17.5
Oil viscosity: mm ² /s@ 40°C	220
Dropping point °C	150 min.
Flowpressure test @ -30°C	Pass.
Application temperature °C	-25 to +110
Colour	Dark brown
Structure	smooth
Specific Gravity @ 15.6°C.	0.950

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
Apr. 15, 2004	604/03	AdG	F SF Gr

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.