

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants – Transmission Oils- Automotive.

Version: 224/01

SynPower DCT VA fluid

Premium fully synthetic transmission fluid for Volkswagen, Audi and Skoda passenger cars and vans with a DSG gearbox (Dual Clutch Transmission).

Valvoline SynPower DCT fluid provides outstanding protection and lubrication of the Dual Clutch Transmission gearbox over a wide temperature range.

Approvals/Performance levels

VW TL 521 82
VW G 052 182 A2
VW G 052 182 A6

Applications

Especially for DSG gearboxes of passenger cars and vans with the Volkswagen DSG transmission.

Suitable for some models of Audi, Skoda, Seat, and Lamborghini with VW DSG transmission.

DSG transmissions and transaxles type 02E (DQ 250), and OBT (DQ 500), with wet clutches.

The product is not meant for dry clutch DSG type OAM, 02M, 02Q, 02S.

Do not mix with other transmission and gear oils.

Features and Benefits

Superior protection

Optimum protection against wear and tear, also under high stress working conditions. Modern additives protect against corrosion, oxidation, foam, and deposits.

Breakdown resistance

Synthetic base oils and a highly balanced additive system avoid breakdown situations even after long-time use.

Consistent viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long term multigrade advantages. Exactly the right friction properties under cold and hot driving circumstances.

Fuel Economy

Dual Clutch Transmissions provide improved fuel consumption over conventional transmissions. Valvoline Synpower DCT is specially designed for use in DCT gearboxes and provides long lubricant life and long term DCT durability.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SynPower DCT Fluid	
SAE Viscosity Grade	
Viscosity , mm ² /s @ 100 °C. ASTM D-445	7.3
Viscosity , mm ² /s @ 40 °C. ASTM D-445	36.3
Viscosity Index ASTM D-2270	173
Viscosity , mPa.s -40°C. ASTM D-2983	11900
Pour Point , °C ASTM D-5950	-51
Specific Gravity @ 15.6°C. ASTM D-4052	0.845
Flash Point , COC, °C. ASTM D92	224

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 224/00

This information only applies to products manufactured in the following location(s): Europe

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.