



Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VPS Engine Flush

VPS1/002

Dissolves sludge and power robbing deposits

Cleans the engine in 5 minutes

Opens restricted oil passages

Frees sticky lifters

Improves oil circulation

Safe for gaskets and other seals

APPLICATION

VPS Engine Flush dissolves sludge gently. Some engine flushes are too strong. They can remove deposits too fast and allow dislodged contaminants to clog vital oil passages. Since VPS Engine Flush is mixed with the used motor oil and allowed to clean for five minutes in an idling engine, thick deposits may not be totally removed. Hard carbon and varnish will not be affected by VPS Engine Flush. Since VPS Engine Flush contains no chlorinated solvents, it is safe for use. VPS Engine Flush will not harm gaskets or other seals if used as directed. Always follow label directions. For engines that have accumulated deposits for 160.000 km. or more, it is recommended that the oil screen should be checked for blockage before using VPS Engine Flush.

EASY TO USE

Before changing the used motor oil and the oil filter, add VPS Engine Flush to the motor oil and allow the engine to run at normal idle speed for 5 minutes. After 5 minutes, stop the engine and drain the crankcase. Replace the filter and refill the crankcase with fresh oil. Do not drive the vehicle or race the engine until the crankcase has been drained and refilled with fresh motor oil.

TECHNICAL DATA

Appearance	Bright & Clear
Flash Point PMCC	83°C.
Specific Gravity at 15°C.:	0.805

COMMENT

VPS Engine Flush can be used in diesel or petrol powered vehicles.
Collect and dispose of used motor oil in accordance with all local environmental regulations.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.