



# Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

## VPS SynPower™ Diesel Fuel System Cleaner

## VPS3/003

**Cleans the entire diesel fuel injection system**  
**Reduces emissions of sootparticles**  
**Disperges Gum and Varnish / Protects against corrosion**  
**Prevents forming of gel deposits / Keeps injectors clean**  
**Lubricates injectors and fuelpumps if running on low sulphur diesel**  
**Fulfils the European Diesel Fuel Norm EN 590.**

### Applications

With the introduction of the yearly car inspection, measuring soot particles is now mandatory, and the use of low sulphur diesel fuel is becoming more common. These environmental measures however have great consequences for car owners, and especially for higher mileage cars. Many times a higher soot particles emission is the result of incomplete combustion. The incomplete combustion can be caused by a filthy air intake system, fuel injectors with dirt deposits, or lower compression.

VPS SynPower Diesel Fuel System Cleaner can be the solution for these problems, possibly in combination with Valvoline Engine Flush. Together these products provide a thorough cleaning of the engine and the fuel injection system, resulting in optimum combustion.

With this, the performance of the engine will be much improved and the soot emissions will be much reduced. The use of a high quality motor oil like MaxLife™ 10W-40 will keep the engine clean and in optimum condition.

### Easy to use

Add VPS SynPower Diesel Fuel System Cleaner to the fuel tank before refilling.  
The content of the bottle (350 ml) is enough for 1 passenger car fuel tank.

### Technical data

Appearance	Clear yellow liquid
Flash Point:	80°C.
Specific Gravity at 15°C.:	0.85
Package size:	350 ml.

### Comment

Flammable liquid  
Keep out of the reach of children

This information only applies to products manufactured in the following location(s): Europe.

Effective Date:	Replaces:	Author's Initials:	Code:
June 2010	VPS3/002	AdG	

™ Trademark of Ashland or its subsidiaries, registered in various countries ©2010, Ashland Inc.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.